

Watercolors [wôdər kælərs]

The masters of watercolor—Albrecht Durer, Georgia O’Keefe, John Singer Sargent, William Turner, and James Whistler—created nuanced paintings rich with emotion. The Watercolors ceramic collection by Lunada Bay Tile pays homage to these famous artists through varied hues. Like miniature works of art, the tiles express a handcrafted, artisanal aesthetic through carefully curated color, from delicate to vibrant. Designed for creative placement in a variety of spaces, the series is available in three formats: Picket, Post and a coordinating liner.

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application		Suitable		Interior	Exterior
Interior Wall/Backsplash		Yes	Shower	No	No
Fireplace/Cooktop Surround		Yes *	Steam Shower	No	N/A
Shower Wall		Yes	Light Residential	Yes	No
Steam Shower		Yes	Residential	No	No
Exterior Wall		Yes	<i>DCOF Value of ≥0.42 is accepted value for use in commercial applications. A 137.1-2018</i>		
Pool, Spa or Water Feature (fully submerged)		No			
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Piece)	Packaging (Per Box)	Standards Methods		
Picket 3 ½ x 6 to 9 ½" Hex	0.188	20 Pieces/3.76 SF	Breaking Strength	ASTM C-648	>450 PSI
Post 3 ½ x 9 ½"	0.232	20 Pieces/4.64 SF	Water Absorption	ASTM C-373	Vitreous ≥0.5%-≤3.0%
Liner ¾ x 9 ½"		80 Pieces/Box	Chemical Resistance	ASTM C-650	Unaffected
			Freeze/Thaw	ASTM C-1026	Unaffected
			Warpage	ASTM C-485	± 0.26%/± 1.5mm
Shade Variation		Grout Joint Recommendation		NOTES	
V1 - V3 Moderate Variation		1/8" (3 mm)		<p>Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).</p>	
MAINTENANCE					
<p>A routine cleaning of Watercolors tile can be done with light duty, diluted close to neutral pH detergent cleaner.</p>					

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. Not recommended for placement inside a firebox.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.