



Allegato alla Dichiarazione di Prestazione
Attachment to Declaration of Performance
Annexe à la déclaration de performance
Anhang der Leistungserklärung
Anexo a la Declaración de Performance
Załącznik do deklaracji właściwości użytkowych
A Teljesítmény Nyilatkozat kiegészítő táblázata
Bijlage bij de prestatieverklaring
Navezanost na izjave o lastnostih
Aneks Izjave o svojstvima
No. FLORIM 001

Tabella - Scivolosità (dove richiesto dalla legislazione)
Table - Slipperiness (where required by regulation)
Table - Glissement (si requis par la loi)
Tabelle - Rutsicherheit (wo erforderlich durch die Gesetzgebung)
Tabla - Deslizamiento (donde sea requerido por ley)
Tabela - Poslizgowosc (gdzie wymagane przez prawo)
Táblázat - Csúszásmentesség (ahol jogszabály szerint szükséges)
Tabel - Antislipwaarde (indien door de wetgever vereist)
Tabela - Drsnosti (samo ko tako zahteva državna zakonodaja)
Tablica - Otpornost na klizanje (gdje je ta zakonski zatraženo)
Rev. 13 del/of/de/vom/de/a 23.12.2019

Marchio / Brand / Marque / Marke / Marca / Znak handlowy / Márka / Merk / Znamka / Trgovačka marka

CASA DOLCE CASA

Serie / Series / Kolekcja / Serija	CENT/ST 16165:2012 Annex B α_{SHOD}	BCRA DM 236/1989 (ITA)	DIN 51130 (DE)	Documento basico SU 3/2006 (ESP)
ARTWORK glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
ARTWORK matte	α da 6° a 10°	N.P.D.	R9	N.P.D.
ARTWORK R+PTV	α da 11° a 19°	>0,4	R10	N.P.D.
COLLECTION 01	α da 11° a 19°	N.P.D.	R10	Classe 1
FLAGSTONE 2.0 glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
FLAGSTONE 2.0 matte	α da 11° a 19°	N.P.D.	R10	N.P.D.
FLAGSTONE 2.0 strutturato	α da 20° a 27°	>0,4	R11	N.P.D.
ICON OUTDOOR	α da 20° a 27°	>0,4	R11	N.P.D.
MOTION	α da 6° a 10°	N.P.D.	R9	N.P.D.
MOTION strutturato	α da 20° a 27°	>0,4	R11	Classe 3
NEUTRA 6.0 tinte unite	N.P.D.	N.P.D.	N.P.D.	N.P.D.
NEUTRA 6.0 tinte unite grip	α da 20° a 27°	>0,4	R11	N.P.D.
ONYX & MORE GLOSSY	N.P.D.	>0,4	N.P.D.	N.P.D.
ONYX & MORE SATIN	N.P.D.	>0,4	N.P.D.	N.P.D.
ONYX & MORE STRUTTURATO	α da 11° a 19°	>0,4	R10	Classe 1
PIETRE 3 naturale	α da 11° a 19°	>0,4	R10	N.P.D.
PIETRE 3 strutturato	α da 20° a 27°	>0,4	R11	N.P.D.
PIETRE 3 strutturato 20 mm	α da 20° a 27°	>0,4	R11	N.P.D.
PIETRE/2 naturale	α da 11° a 19°	>0,4	R10	N.P.D.
STONES & MORE 2.0 matte (stone burl white-)	α da 11° a 19°	>0,4	R10	N.P.D.
STONES & MORE 2.0 smooth	α da 6° a 10°	>0,4	R9	N.P.D.
STONES & More 2.0 glossy	N.P.D.	>0,4	N.P.D.	N.P.D.
STONES & MORE 2.0 matte (Stone Marfil-Ston	α da 6° a 10°	>0,4	R9	N.P.D.
STUDIOS OF CASAMOOD grip	α da 20° a 27°	>0,4	R11	N.P.D.
STUDIOS OF CASAMOOD grip 20 mm	α da 20° a 27°	>0,4	R11	N.P.D.
STUDIOS OF CASAMOOD matte	α da 11° a 19°	N.P.D.	R10	N.P.D.
URBAN STYLE	α da 11° a 19°	>0,4	R10	N.P.D.
URBAN STYLE STRUTTURATO	α da 20° a 27°	>0,4	R11	N.P.D.



FLORIM CERAMICHE S.p.A. a socio unico
VIA CANALETTO 24 / 41042 FIORANO MODENESE (MO) ITALY
T. +39 0536 840111 / F. +39 0536 840322
www.florim.com




URBAN STYLE STRUTTURATO 20 MM	α da 20° a 27°	>0,4	R11	N.P.D.
WOODEN TILE WALNUT naturale	α da 6° a 10°	>0,4	R9	Classe 1
WOODEN TILE naturale	α da 11° a 19°	>0,4	R10	N.P.D.
WOODEN TILE strutturato	α da 20° a 27°	>0,4	R11	Classe 2



FLORIM CERAMICHE S.p.A. a socio unico
VIA CANALETTO 24 / 41042 FIORANO MODENESE (MO) ITALY
T. +39 0536 840111 / F. +39 0536 840322
www.florim.com

CE MARKING

Fine porcelain stoneware
Glazed porcelain stoneware
Coloured body porcelain stoneware

	
FLORIM CERAMICHE S.p.A., Via Canaletto, 24 - 41042 Fiorano Modenese (MO) – Italia	
05 FLORIM 001	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5 \%$, for internal and external walls and floorings	
Reaction to fire	A1 _{FL} /A1
Release of dangerous substances, for:	
- Cadmium	NPD
- Lead	NPD
Breaking strength	> 1300 N
Slipperiness, as:	See table attached
Tactility	NPD
Bond strength/adhesion, for:	
Cementitious adhesive, type C2	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal use:	Pass
- external use: freeze-thaw resistance	Pass