## **AURA**

Aura mixes a natural surface with a thin layer of color, giving the sense of an impressionist painting with a hint of metal peeking through. A member of our Metallics Collection, Aura is available in Green, Beige, or Blue tones and stocked in 24" x 24" porcelain field tiles.





## **AURA**













Blue Matte Beige Matte Green Matte

APPLICATIONS								ATTRIBUTES	VAF
INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	DCOF <sup>2</sup>	V1 VZ
Medium Traffic Commercial	All	Yes, including steam	Yes <sup>1</sup>	No	Yes, including freeze thaw	Yes, non-freeze thaw	Yes	0.62 0.67 0.66	L

VARIATION
V1 V2 V3 V4

24" × 24" × <sup>3</sup>/8"

Matte

INSTALLATION/MAINTENANCE											
SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT		
Ardex X7 Microtec Fiber Reinforced Mortar <sup>3</sup>	Ardex FL Rapid Set Sanded <sup>4</sup>	½" minimum	Ardex 8+9	Ardex SX	AquaMix Grout Release	AquaMix Concentrated Stone & Tile Cleaner	TCNA Handbook	33% max. offset	Sample <sup>5</sup>		

## NOTES

- <sup>1</sup> Mosaic formats only
- $^2$  The standard requires a minimum wet DCOF Acutest value greater than 0.42 for ceramic tiles (inclusive of porcelain) for level interior spaces expected to be walked upon when wet.
- $^3\, Alternate$  mortar Ardex X5 Medium Bed Mortar or Mapei Ultraflex LFT
- <sup>4</sup>Alternate grout Mapei Flexcolor CQ or Mapei Ultracolor Plus FA
- $^{5}\mbox{Layout}$  for overview of material before installation.

30 faces

Tech Note: Porcelains that meet the DCOF standard may have a more abrasive surface that might show dirt or debris. Remove with soap, water and firm scrubbing in order to clean. Consider this in the selection process.

