

# WHITE SAND

---

White Sand is a beautiful neutral beige marble with delicate tonal veining and a smooth background.  
Stocked in a variety of honed and polished mosaics and field tile.



Ceramic Matrix

An Architectural Surfaces Company



# WHITE SAND



*12" x 24" Field Tile  
Polished & Honed*




*24" x 24" Field Tile  
Polished*




*11 3/8" x 12 1/8" Hexagon Mosaic  
Polished*



*Raked 12" x 24" Textured Field Tile*



*24" x 48" Field Tile  
Honed Finish*



APPLICATIONS									VARIATION				TAILORED TO CUSTOMIZATION <sup>1</sup>	
INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	FIREPLACE SURROUND	<div><div>V1</div><div>V2</div><div>V3</div><div>V4</div></div> <div></div>				CARPET CUTTING	
Light/Medium Traffic Commercial	All	Yes, including Steam	Yes, in Mosaics Format Only	No	Yes, including freeze thaw	No	Yes	Yes					FIELD	
														FINISH
														MOSAIC
														SADDLE
														VANITY TOP
														WATERJET
INSTALLATION/MAINTENANCE										AVAILABLE SIZES				
SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT	<div><div></div><div></div></div>				
Mapei Ultraflex LFT <sup>2</sup>	Ardex FG-C Microtec Unsanded <sup>3</sup>	1/16" minimum	Ardex 8+9 <sup>4</sup>	Ardex SX <sup>5</sup>	AquaMix Sealer's Choice Gold	AquaMix Concentrated Stone & Tile Cleaner <sup>6</sup>	TCNA Handbook	No	Sample <sup>7</sup>					
NOTES														
<sup>1</sup> 24"x48" Field Tile - No														
<sup>2</sup> Alternate mortar - Grainrapid 2 - Part System or Ardex X77 Microtec Fiber Reinforced Mortar														
24"x48" Field Tile mortar - Mapei Kerapoxy 410														
<sup>3</sup> Alternate grout - Mapei Ultracolor Plus or Mapei Keracolor CQ														
24"x48" Field Tile grout - Mapei Ultracolor Plus FA or Mapei Flexcolor CQ														
<sup>4</sup> 24"x48" Field Tile membrane - Mapei Mapelastic AquaDefense														
<sup>5</sup> 24"x48" Field Tile caulk - Mapei Keracaulk Sanded														
<sup>6</sup> 24"x48" Field Tile cleaner - AquaMix Concentrated Cleaner														
<sup>7</sup> Layout for overview of material before installation.														
Tech Note: We strongly suggest a dry layout and 25% overage of material to allow for proper blending.														
Product must be installed in accordance with current TCNA Handbook Stone Methods. We strongly suggest a dry layout and 25% coverage of material to allow for proper blending. The Natural Stone Institute recommends installing resin-backed stone with epoxy-based setting materials. Consult your setting materials manufacturer for specific products.														



Ceramic Matrix

An Architectural Surfaces Company