

DECLARATION OF PERFORMANCE COLLECTION ROMA

n° CPR_01

1. Unique identification code of the product type: **Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$**
2. Intended uses: **for internal and external walls and floorings**
3. Name or registered trade mark, and contact address of the manufacturer:
Fap ceramiche, via Ghiarola Nuova, 44 – 41042 Fiorano Modenese (MO) ITALY
4. System(s) of assessment and verification of constancy of performance (AVCP): **System 4**
5. Name and identification number of notified laboratory, if relevant: **not relevant**
6. Declared performance

Essential Characteristics	Performance	Harmonised technical specification
Reaction to fire	A1FL/A1	EN 14411: 2012
Release of dangerous substance: (only for GL ceramic tiles)		
- Cadmium	npd	
- Lead	npd	
Breaking strenght (thickness $\geq 7,5$)	≥ 1300 N	
Breaking strenght (thickness $< 7,5$)	≥ 700 N	
Slipperiness	See table attached	
Tactility	npd	
Bond strenght/adhesion	npd	
Thermal shock resistance	Pass	
Durability for	Pass	
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Norberto Marzani
Marketing Manager

Fiorano Modenese 10/04/2016

Tabella - Scivolosità rev.12/09/2016

Serie	Prodotto	DIN 51130 (DE)	BCRA D.M. 236/1989 (ITA)	D.B. SUA 3/2006 (ESP)
Roma	Calacatta Matt	R9	> 0,40	npd
	Grafite Matt	R9	> 0,40	npd
	Imperiale Matt	R9	> 0,40	npd
	Pietra Matt	R9	> 0,40	npd
	Statuario Matt	R9	> 0,40	npd
	Travertino Matt	R9	> 0,40	npd
	Calacatta Lux	npd	> 0,40	npd
	Grafite Lux	npd	> 0,40	npd
	Imperiale Lux	npd	> 0,40	npd
	Pietra Lux	npd	> 0,40	npd
	Statuario Lux	npd	> 0,40	npd
	Travertino Lux	npd	> 0,40	npd